
List of Figures

1.1	Tooth of the earth moving machine	14
1.2	Working body of the soil disintegrator	15
1.3	Scheme of soil cleavage by the cutting element	16
1.4	Tooth of the earth moving machine	17
1.5	Soil disintegrator tip	18
2.1	Particle motion pattern	29
3.1	Differentiated scheme for determining the power and energy parameters when cutting soils	36
3.2	Dependence of pressures on the front face of the cutting element, normal to the direction of cutting speed, on the depth of cut for loosely bound soils: <i>a</i> – nature of the dependence $\sigma=f(h)$; <i>b</i> – approximation of dependence $P=f(h)$	42
3.3	Pressure distribution on the front face of the cutting element along the width of the tooth $b, \sigma(b)$: <i>a</i> – nature of the dependence $\sigma(b)$; <i>b</i> – approximation of dependence $\sigma(b)$	42
3.4	The dependence of normal stresses in the soil in contact with the front face of the cutting element when cutting cohesive plastic soils: <i>a</i> – nature of the dependence $\sigma=f(h)$; <i>b</i> – approximation of dependence $\sigma=f(h)$	42
3.5	The influence of the cutting angle on the distribution of normal stresses on the front face of the tool (cutting lead) [13]: <i>a</i> – $\delta=100^\circ$; <i>b</i> – $\delta=90^\circ$; <i>c</i> – $\delta=80^\circ$	43
3.6	A fragment of the lateral surface of the working body with the developed elements of differential design	45
3.7	Developed element of differential design	46
3.8	Design schemes: <i>a</i> – with the installation of a vibration exciter on a reactive mass m_1 ; <i>b</i> – with the installation of the vibration exciter on the working body m_2	48
3.9	Amplitude (<i>a</i>) and phase-frequency characteristics and static characteristics (<i>b</i>) of the machine and engine for the circuit (Fig. 3.8, <i>a</i>): $x=0.125$; $\beta_1=0.02$; $\beta_2=0.15$	51
3.10	Amplitude and phase-frequency characteristics and static characteristics of a machine and engine for a circuit (Fig. 3.8, <i>b</i>): at $x=0.125$; $\beta_1=0.02$; $\beta_2=0.15$	53

4.1	Scheme of the physical model of the three-mass vibratory jaw crusher: <i>a</i> – 3D model of three mass vibratory crushers; <i>b</i> – control unit	55
4.2	Experimental device of a vibratory crusher	55
4.3	Schematic diagram of a data acquisition system	56
4.4	Appearance of the data acquisition system	56
4.5	Vibrograms of the third mass of the crusher during its operation with the material ($\omega=75.36$ rad/s, $F=2130$ N, $c_2=219052$ N/m)	57
4.6	Vibrograms of mass oscillations of the crusher during its operation with material ($\omega=104.667$ rad/s, $F=4111$ N, $c_2=219052$ N/m): <i>a</i> – movement of the second mass; <i>b</i> – movement of the third mass	57
4.7	Vibrograms of mass oscillations of the crusher when working with material ($\omega=104.667$ rad/s, $F=4111$ N, $c_2=234438$ N/m): <i>a</i> – movement of the second mass; <i>b</i> – movement of the third mass	58
4.8	Design diagram of the KIBI knocker	60
4.9	Scheme of the device stand for recording the striker movement with teeth upon impact: <i>a</i> – scheme of the device, <i>b</i> – example of recording the dependence $S(t)$	62
4.10	Experimental graphs of the dependence of the average tangential cutting force on the parameters of the shock load	63
4.11	Comparison of the resistance forces of quasistatic and dynamic (impact) cutting versus cut thickness at a constant cutting angle $\delta=45^\circ$	63
4.12	Design 3D model of vibration unit for the formation and compaction of concrete mixtures	67
4.13	General view of the vibration unit	69
4.14	The vibration exciter with unbalance position sensor	69
4.15	Sensor: <i>a</i> – displacements; <i>b</i> – deformations	70
4.16	Layout of measurement sensors	70
4.17	General view of the experimental unit	71
4.18	Oscillogram of vibration unit movement	71
4.19	Oscillogram of the vibration unit movement at an oscillation frequency of 12.5 Hz	72
4.20	Oscillogram of the vibration unit movement at an oscillation frequency of 18.6 Hz	72
4.21	Oscillogram of the vibration unit movement at an oscillation frequency of 24.3 Hz	72
4.22	Deformations of the forming surfaces at an oscillation frequency of 24.3 Hz (sensors 10, 11, 12 (Fig. 4.16))	73
4.23	Deformations of the forming surfaces at an oscillation frequency of 24.3 Hz (sensors 3, 4, 5 (Fig. 4.16))	73